

CLAIMS

What is claimed is:

5 1. A vision-based identification apparatus comprising:

a host vehicle;

wherein said host vehicle is equipped with a plurality of elements including:

- 10 i) an image capture device element; operatively interconnected with;
- ii) an image signal processor element; which is operatively interconnected with;
- iii) a matching processor element; which is also operatively interconnected with;
- iv) a radar transceiver element;

wherein the image capture device is configured to provide a time based sequence of data frames to the image signal processor and the image signal processor provides a processed image signal to the matching processor, and

15 wherein the data frames include a two dimensional array of pixel elements; and

wherein the radar transceiver is configured to provide a radar signal to the matching processor, and

wherein the matching processor combines the processed image signal and the radar signal, whereby the combined signals complement each other and allow the apparatus to

20 effectively identify objects likely to be misidentified as collision threats.

2. The vision-based identification apparatus of claim 1, wherein the image capture device is a video camera responsive to electromagnetic radiation substantially in at least

one of the regions selected from the group consisting of the visible region, and the infrared region.

3. The vision-based identification apparatus of claim 1, wherein the time based sequence
5 of data frames include a plurality of data elements including at least one horizontal edge;
and

wherein each horizontal edge is identified based on a plurality of pixels having a
substantially similar electromagnetic radiation response across a plurality of substantially
horizontally aligned pixels; and

10 wherein the image signal processor extracts horizontal edges, from the time based
sequence of data frames, in the form of edge pixels, and

wherein the edge pixels are projected in each row of the data frames, to get a horizontal
edge projection in the sequence of data frames; and

15 wherein each horizontal edge projection may be tracked in time based on the horizontal
edge projection's sequential appearance in the data frames.

4. The vision-based identification apparatus of claim 3, wherein horizontal edge
projections may be tracked in time by recording sequential data frames and matching
horizontal edge projections in the sequential data frames while allowing, in the sequential

20 data frames, for minor variations from, in at least one of the following categories:

- i. the relative position of the horizontal edge projection in the frame;
- ii. the relative orientation of the horizontal edge projection in the frame; and
- iii. the relative length of the horizontal edge projection; and

wherein at least one new tracking sequence can exist for horizontal edge projections that have predefined characteristics but were not present in prior data frames.

5. The vision-based identification apparatus of claim 4, wherein allowed, minor

5 variations in the sequential data frames provide data that allows for the determination and recordation of distance traveled since the beginning of each horizontal edge projection tracking sequence, and

wherein horizontal edge projection tracks are sorted based on at least one of the following;

- 10 i) the duration of image inputs that the horizontal edge projection track records,
- ii) the average length of the horizontal edge projection, and
- iii) whether the horizontal edge projection track at current image frame is in an updating mode, a non-updating mode, or is a new horizontal edge projection.

15 6. The vision-based identification apparatus of claim 4 wherein the horizontal edge projection tracks are compared with predetermined parameters to determine if tracking possibilities exist;

if tracking possibilities exist then the vision-based identification apparatus is utilized to track substantially horizontal edges through successive image inputs.

20 7. The vision-based identification apparatus of claim 6 wherein the predetermined parameters include at least one of the following;

- i. the number of successive image inputs having horizontal edge projection tracks, and
- ii. the magnitude of the horizontal edge projection tracks.

5 8. The vision-based identification apparatus of claim 4 wherein if no tracking possibilities exist, tracking may still occur for a pre-specified number of image inputs without tracking possibilities before the tracked horizontal edge projection track is discarded.

10 9. The vision-based identification apparatus of claim 1 wherein tracking of horizontal edge projection vectors is assisted by using at least one of the following:

- i) vertical motion compensation;
- ii) forward motion compensation;

15 wherein vertical motion compensation helps predict where tracked horizontal edge projection vectors will be located on successive image inputs by compensating for vertical motion, and

wherein the forward motion compensation helps predict where tracked horizontal edge projection vectors will be located on successive image inputs by compensating for forward motion.

20 10. The vision-based identification apparatus of claim 9 wherein forward motion compensation is achieved by using at least two previous points from the image input on the tracked horizontal edge projection tracks, immediately before the image input that

requires forward motion compensation for tracked horizontal edge projection vectors
location prediction.

11. The vision-based identification apparatus of claim 9 wherein vertical motion is

5 determined by:

- i. extracting vertical slices of the image input; and
- ii. extracting one dimensional optical flow profiles of relative intensity of the
vertical slices; and
- iii. averaging the optical flow of all vertical slices.

12. The vision-based identification apparatus of claim 11 wherein the vertical slices are
extracted from each image input, and
the relative extreme negative intensities relate to a change from light to dark of an
apparent horizon.

13. The vision-based identification apparatus of claim 11 wherein the extreme negative
intensities' average variation between rows on successive image inputs is an indicia of
how an image collection device is moving vertically relative to at least one of the
following:

- 20 i. an apparent horizon; and
- ii. a distinct feature in the distance.

14. The vision-based identification apparatus of claim 1 wherein the signal input from the image capture device to the image signal processor is a single horizontally centered window of the image signal input from the image capture device.

15. The vision-based identification apparatus of claim 14 wherein the single horizontally centered window is set at a predetermined width and a predetermined height and wherein the single horizontally centered window can be adjusted either left or right based on steering wheel position, or lane information.

16. The vision-based identification apparatus of claim 14 wherein successive horizontal edge projection tracks have a length in excess of a predetermined length.

17. The vision-based identification apparatus of claim 14 wherein if no tracking possibilities exist, a tracking protocol will be allowed to remain in operation for a pre-specified number of image inputs without tracking possibilities before the tracked horizontal edge projection track is discarded.

18. A vision-based identification method comprising the steps of:
providing a host vehicle; and

equipping the host vehicle with a plurality of elements including:

- i) an image capture device element; operatively interconnected with;
- ii) an image signal processor element; which is operatively interconnected with;
- iii) a matching processor element; which is also operatively interconnected with;

iv) a radar transceiver element;

wherein the image capture device is configured to provide a time based sequence of data frames to the image signal processor and the image signal processor provides a processed image signal to the matching processor; and

5 wherein the data frames include a two dimensional array of pixel elements; and

wherein the radar transceiver is configured to provide a radar signal to the matching processor; and

wherein the matching processor combines the processed image signal and the radar signal, whereby the combined signals complement each other and allow for the effective
10 identification of objects likely to be misidentified as collision threats.

19. A vision-based identification method as set forth in claim 18, wherein the image capture device element is a video camera responsive to electromagnetic radiation substantially in at least one of the regions selected from the group consisting of the
15 visible region, and the infrared region.

20. A vision-based identification method as set forth in claim 18, wherein the time based sequence of data frames include a plurality of data elements including at least one horizontal edge; and

20 wherein each horizontal edge is identified based on a plurality of pixels having a substantially similar electromagnetic radiation response across a plurality of substantially horizontally aligned pixels; and

wherein the image signal processor extracts horizontal edges, from the time based sequence of data frames, in the form of edge pixels; and
wherein the edge pixels are projected in each row of the data frames, to get a horizontal edge projection in the sequence of data frames; and
5 wherein each horizontal edge projection may be tracked in time based on the horizontal edge projection's sequential appearance in the data frames.

21. A vision-based identification method as set forth in claim **20**, wherein horizontal edge projections may be tracked in time by recording sequential data frames and matching
10 horizontal edge projections in the sequential data frames while allowing, in the sequential data frames, for minor variations from, in at least one of the following categories:

- i. the relative position of the horizontal edge projection in the frame;
- ii. the relative orientation of the horizontal edge projection in the frame; and
- iii. the relative length of the horizontal edge projection; and

15 wherein at least one new tracking sequence can exist for horizontal edge projections that have predefined characteristics but were not present in prior data frames.

22. A vision-based identification method as set forth claim **21**, wherein allowed, minor variations in the sequential data frames provide data that allows for the determination and
20 recordation of distance traveled since the beginning of each horizontal edge projection tracking sequence, and
wherein horizontal edge projection tracks are sorted based on at least one of the following;

- i. the duration of image inputs that the horizontal edge projection track records;
- ii. the average length of the horizontal edge projection; and
- iii. whether the horizontal edge projection track at current image frame is in an updating mode, a non-updating mode, or is a new horizontal edge projection.

5

23. A vision-based identification method as set forth in claim **21** wherein the horizontal edge projection tracks are compared with predetermined parameters to determine if tracking possibilities exist;

if tracking possibilities exist then the vision-based identification apparatus is utilized to track substantially horizontal edges through successive image inputs.

24. A vision-based identification method as set forth in claim **23** wherein the predetermined parameters include at least one of the following;

- i. the number of successive image inputs having horizontal edge projection tracks;
- and
- ii. the magnitude of the horizontal edge projection tracks.

25. A vision-based identification method as set forth in claim **21** wherein if no tracking possibilities exist, tracking may still occur for a pre-specified number of image inputs without tracking possibilities before the tracked horizontal edge projection track is discarded.

26. The vision-based identification method of claim 18 wherein tracking of horizontal edge projection vectors is assisted by using at least one of the following:

- i) vertical motion compensation; and
- ii) forward motion compensation;

5 wherein vertical motion compensation helps predict where tracked horizontal edge projection vectors will be located on successive image inputs by compensating for vertical motion, and

wherein the forward motion compensation helps predict where tracked horizontal edge projection vectors will be located on successive image inputs by compensating for
10 forward motion.

27. The vision-based identification method of claim 26, wherein forward motion compensation is achieved by using at least two previous points from at the image input on the tracked horizontal edge projection tracks, immediately before the image input that
15 requires forward motion compensation for tracked horizontal edge projection vectors location prediction.

28. A vision-based identification method as set forth in claim 26, wherein vertical motion is determined by:

- 20 i. extracting vertical slices of the image input; and
- ii. extracting one dimensional optical flow profiles of relative intensity of the vertical slices; and
- iii. averaging the optical flow of all vertical slices.

29. A vision-based identification method as set forth in claim **28**, wherein the vertical slices are extracted from each image input, and the relative extreme negative intensities relate to a change from an electromagnetic radiation emission region having a greater intensity to an electromagnetic radiation emission region of lower intensity of an apparent horizon.

30. A vision-based identification method as set forth in claim **28**, wherein the extreme negative intensities' average variation between rows on successive image inputs is an indicia of how an image collection device is moving vertically relative to at least one of the following:

- i. an apparent horizon; and
- ii. a distinct feature in the distance.

31. A vision-based identification method as set forth in claim **18**, wherein the signal input from the image capture device to the image signal processor is a single horizontally centered window of the image signal input from the image capture device.

32. A vision-based identification method as set forth in claim **31**, wherein the single horizontally centered window is set at a predetermined width and a predetermined height; and wherein the single horizontally centered window can be adjusted either left or right based on steering wheel position, or lane information.

33. A vision-based identification method as set forth in claim **31**, wherein successive horizontal edge projection tracks have a length in excess of a predetermined length.

- 5 34. A vision-based identification method as set forth in claim **31** wherein if no tracking possibilities exist, a tracking protocol will be allowed to remain in operation for a pre-specified number of image inputs without tracking possibilities before the tracked horizontal edge projection track is discarded.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000